PRODUCT SERIES 产品系列


行星减速箱 Planetary Gearbox PG36



外壳材质 (Housing material)：…… metal
背隙,无负荷时 (Backlash,at no-load)：…… ≤1.5°
轴承型号 (Bearing at output)：…… Ball bearings
径向间隙 (Radial play of shaft)：…… ≤0.1 mm
轴向间隙 (Thrust play shaft)：…… ≤0.2 mm
齿轮箱适用于RS-528，BL36，RS-555和ZY36马达。
(The gear box can apply to RS-528,BL36,RS-555 and ZY36 motors)

⚠ 马达瞬间允许扭矩150kgf·cm。当使用低转速、高速比时，请选用低功率马达，请做好保护措施。
(When the motors using at low speed , high gear ratio will cause gear motor torque more than 150kgf.cm.At this torque the gears will be broken easily. Be noted.)

外形尺寸图/Appearance size



马达齿轮参数/Pinion Specifications

模数 Module	0.48	0.48	0.48	
齿数 NO.of teeth	11	17	17	
压力角 Pressure angle	20°	20°	20°	
孔径 Hole diameter	ϕ 1.98	ϕ 2.28	ϕ 3.14	

使用温度范围/Operating temperature range：-30℃~+85℃
使用相对湿度/Operating relative humidity：20%~85%RH

标准减速比参数/Gearboxes Specifications

减速比 Raduction ratio	精确减速比 Raduction absolute	额定允许扭矩 Rated tolerance torque	极限扭矩 Max breaking torque	效率 Efficiency	级数 Number of stages	齿轮箱长度 Gearbox length "L" mm	输入输出方向 Input/output direction
3.7，5.2	$3^{12/17}$，$5^{2/11}$	20.0kgf·cm	60.0kgf·cm	90%	1	25.1	=
13.7，19.2，26.9	$13^{3/4}$，$19^{38/187}$，$26^{103/121}$	50.0kgf·cm	150.0kgf·cm	81%	2	32.3	=
50.9，71.2	$50^{4397/4913}$，$71^{524/3179}$	100.0kgf·cm	300.0kgf·cm	73%	3	38.5	=
99.5，139	$99^{1044/2057}$，$139^{184/1331}$	100.0kgf·cm	300.0kgf·cm	73%	3	38.5	=
188，264，369	$188.^{611}$，$263.^{729}$，$369.^{763}$	100.0kgf·cm	300.0kgf·cm	65%	4	44.7	=
516，721	$515.^{630}$，$720.^{989}$	100.0kgf·cm	300.0kgf·cm	65%	4	44.7	=
699，997	$698.^{969}$，$977.^{347}$	100.0kgf·cm	300.0kgf·cm	59%	5	50.9	=
1367，1911	$1366.^{593}$，$1910.^{864}$	100.0kgf·cm	300.0kgf·cm	59%	5	50.9	=
2672，3736	$2671.^{901}$，$3736.^{034}$	100.0kgf·cm	300.0kgf·cm	59%	5	50.9	=

○ 以上参数仅做参考，具体以实物为准。
The above parameters are for reference only.

直流行星减速电机
Planetary gear DC motor
PG36555




适用范围/Scope of application

遥控窗帘 | 监控云台 | 自动售货机 | 验钞机 | 硬币退币机 | 点钞机
柔巾机 | 自动门 | 覆膜机 | 自动电视架 | 办公设备 | 家用电器 等等

Remote Control Curtains | Monitor PTZ | Vending Machine | Money Detector | Coin Refund | Order money | Soft Tissue Machine | Automatic door | Laminating machine | Automatic TV stand | Office equipment | Household appliances etc.

外形尺寸图/Appearance size



减速箱清单/Gearbox data

级数 Number of stages	1	2	3	4	5
减速比 Reduction ratio	3.7,5.2	13.7,19.2,26.9	50.9,71.2,99.5,139	188,264,369,516,721	699,977,1367,1911,2672,3736
齿轮箱长度 Gearbox length "L" mm	25.1	32.3	38.5	44.7	50.9
额定扭矩 Max.Running torque	20.0kgf·cm	50.0kgf·cm	100.0kgf·cm	100.0kgf·cm	100.0kgf·cm
损坏扭矩 Gear breaking torque	60.0kgf·cm	150.0kgf·cm	300.0kgf·cm	300.0kgf·cm	300.0kgf·cm
效率 Gearing efficiency	90%	81%	73%	65%	59%

马达清单/Motor data

马达型号 Motor type	额定电压 Rated volt (V)	空载转数 No load speed (rpm)	空载电流 No load current (mA)	额定转数 Rated speed (rpm)	额定电流 Rated current (mA)	额定扭矩 Rated torque (gf.cm)	额定功率 Rated output (W)	堵转扭矩 Stall torque (gf.cm)	堵转电流 Stall current (A)
RS-555123000	12	3000	≤140	2500	≤540	179	4.51	1210	≤3.1
RS-555124500	12	4500	≤200	3950	≤850	183	7.42	1508	≤5.9
RS-555126000	12	6000	≤320	5240	≤1340	215	11.5	1722	≤9.3
RS-555243500	24	3500	≤115	2920	≤450	246	7.5	1762	≤2.7
RS-555244500	24	4500	≤140	3980	≤440	189	7.8	1713	≤3.4
RS-555246000	24	6000	≤140	5300	≤850	284	15.7	2360	≤6.2

注：减速后的输出扭矩=马达扭矩X减速比X齿轮箱效率；输出转速=马达转速/减速比；马达曲线图详见55、56页
本公司可定做各种非标产品，如有需要请来电咨询。
Note: Output torque after deceleration = motor torque X reduction ratio X gearing efficiency;
Output speed = motor speed / reduction ratio; Motor performance curve is shown on Page 55、56
Our company can customize a variety of non-standard products, please contact us.

○ 以上参数仅做参考，具体以实物为准。
The above parameters are for reference only.