PRODUCT SERIES 产品系列


行星减速箱 Planetary Gearbox PG56



外壳材质 (Housing material)：…… metal
背隙,无负荷时 (Backlash,at no-load)：…… ≤1.5°
轴承型号 (Bearing at output)：…… Ball bearings
径向间隙 (Radial play of shaft)：…… ≤0.1 mm
轴向间隙 (Thrust play shaft)：…… ≤0.2 mm
齿轮箱适用于ZY58马达。
(The gear box can apply to ZY58 motors)

⚠ 马达瞬间允许扭矩600kgf·cm。当使用低转速、高速比时，请选用低功率马达，请做好保护措施。
(When the motors using at low speed , high gear ratio will cause gear motor torque more than 600kgf.cm.At this torque the gears will be broken easily. Be noted.)

外形尺寸图/Appearance size



马达齿轮参数/Pinion Specifications

模数 Module	1.0	1.0		
齿数 NO.of teeth	12	15		
压力角 Pressure angle	20°	20°		
孔径 Hole diameter	ϕ 5.97	ϕ 5.97, ϕ 7.96		

使用温度范围/Operating temperature range：-30℃~+85℃
使用相对湿度/Operating relative humidity：20%~85%RH

标准减速比参数/Gearboxes Specifications

减速比 Raduction ratio	精确减速比 Raduction absolute	额定允许扭矩 Rated tolerance torque	极限扭矩 Max breaking torque	效率 Efficiency	级数 Number of stages	齿轮箱长度 Gearbox length "L" mm	输入输出方向 Input/output direction
3.6，4.3	3 3/5，4 1/4	100.0kgf·cm	300.0kgf·cm	90%	1	37.1	=
13，19.2，22.7	12 24/25，19 1/5，22 2/3	200.0kgf·cm	600.0kgf·cm	81%	2	51.0	=
46.7，69	46 82/125，69 3/25	400.0kgf·cm	1200.0kgf·cm	73%	3	64.9	=
102，121	102 2/5，120 8/9	400.0kgf·cm	1200.0kgf·cm	73%	3	64.9	=
198，276	198 36/125，276 57/180	400.0kgf·cm	1200.0kgf·cm	65%	4	78.8	=
326，409，513	326 65/256，409 5/12，513 7/9	400.0kgf·cm	1200.0kgf·cm	65%	4	78.8	=
843，995	842 18/25，994 353/400	400.0kgf·cm	1200.0kgf·cm	59%	5	95.2	=
1567，1966	1566 18/25，1966 2/25	400.0kgf·cm	1200.0kgf·cm	59%	5	95.2	=
2321，3439	2321 1/15，3438 50/81	400.0kgf·cm	1200.0kgf·cm	59%	5	95.2	=

○ 以上参数仅做参考，具体以实物为准。
The above parameters are for reference only.

直流行星减速电机
Planetary gear DC motor
PG56ZY58




适用范围/Scope of application

医疗器械 | 自动售货机 | 纺织机 | 地铁广告牌 | 点钞机
自动门 | 覆膜机 | 碎纸机 | 办公设备 | 家用电器 等等

Medical Equipment | Vending Machine | Textile Machine | Subway Billboard | Banknote Counter | Automatic door | laminating machine shredder | office equipment | household appliances etc.

外形尺寸图/Appearance size



减速箱清单/Gearbox data

级数 Number of stages	1	2	3	4	5
减速比 Reduction ratio	3.6,4.3	13,15.3,19.2	46.7,69,102,121	198,276,326,409,513	843,995,1567,1966,2321,3439
齿轮箱长度 Gearbox length "L" mm	32.1	46.0	59.9	73.8	90.2
额定扭矩 Max.Running torque	100.0kgf·cm	200.0kgf·cm	400.0kgf·cm	400.0kgf·cm	400.0kgf·cm
损坏扭矩 Gear breaking torque	300.0kgf·cm	600.0kgf·cm	1200.0kgf·cm	1200.0kgf·cm	1200.0kgf·cm
效率 Gearing efficiency	90%	81%	73%	65%	59%

马达清单/Motor data

马达型号 Motor type	额定电压 Rated volt (V)	空载转数 No load speed (rpm)	空载电流 No load current (mA)	额定转数 Rated speed (rpm)	额定电流 Rated current (mA)	额定扭矩 Rated torque (gf.cm)	额定功率 Rated output (W)	堵转扭矩 Stall torque (gf.cm)	堵转电流 Stall current (A)
ZY58123000	12	3000	≤444	2600	≤3290	1508	38.1	7594	≤21.1
ZY58243000	24	3000	≤252	2605	≤6252	1562	39.5	8392	≤12.4

注：减速后的输出扭矩=马达扭矩X减速比X齿轮箱效率；输出转速=马达转速/减速比；马达曲线图详见61页
本公司可定做各种非标产品，如有需要请来电咨询。
Note: Output torque after deceleration = motor torque X reduction ratio X gearing efficiency;
Output speed = motor speed / reduction ratio; Motor performance curve is shown on Page 61
Our company can customize a variety of non-standard products, please contact us.

○ 以上参数仅做参考，具体以实物为准。
The above parameters are for reference only.